

# Technical Data Sheet

## Low Sheen



15A Malcolm Crt, Kealba 3021

(03) 9364 4489

ultra.tex@hotmail.com

ABN: 50 119 993 412

### Description

A 100% acrylic water thinned paint that dries to a matt finish and is available in white, pastel and deep accent tones. Superior exterior durability-decorates and protects the surface from extreme weather conditions.

### Uses

This product has excellent opacity using the lightest fast pigments for exterior use. Suitable on a variety of substrates such as brick, cement render, masonry, plasterboard, metal and timber. Use on all exterior surfaces in the home, and on display and feature sign work when a matt finish is required. It may also be used on all interior surfaces.

### Features and Benefits

- Strong adhesion, Resistance to Mould and Algae
- Protects from extreme weather conditions
- Excellent flexibility, crack resistance and has good vapour permeability,
- Tint-able to extensive colour range
- Easy to apply
- Water based

### Suitable Substrates – when properly prepared

- Fresh texture coated surface
- Brick
- Cement render
- Masonry
- Plasterboard
- Metal
- Timber

### Application

- Thoroughly stir and apply with brush, roller or spray. Requires two coats for a perfect finish.

### Application

Under normal drying conditions (above 15° C and low humidity) it will touch dry in 30 minutes and can be recoated after 2 hours. Do not apply if the temperature is below 10°C.

### Surface Preparations

- Ensure the surface is dry and clean of dirt, grease and dust
- **Timber** – No primer is necessary unless the timber is tannin rich in which case apply Acrylic Wood Primer. Sand and dust down all bare timber and fill holes prior to painting
- **Galvanised Iron and Aluminium** – Remove oil and grease with mineral turpentine. Apply acrylic metal primer
- **Iron and steel** – Remove oil, grease and rust. Treat remaining rust with a rust converter then apply acrylic metal primer
- **Brick and Masonry** – Remove all loose and powdery material with a stiff brush and wash down. No primer required
- **Previously painted** – Scrape off all loose and flaking paint and sand glossy surfaces. Wash down with sugar soap. Spot prime metal with appropriate primer. When using deep tone colours such as Process Yellow and Vip Red apply a white or light grey undercoat first. This will ensure true colour and help coverage

Packaged	Coverage / Pail	Thk	
15L Pail	14-16 SqM /Pail	WFT 150-200uM	
Application Tools	20-30 Nap roller		
Clean Up	Clean all tools with water after use		
Appearance	Viscous liquid		
Drying Time (25°C & 50% RH)	Tack Free	Over-coat	Fully Dry
	30 mins	2-3 Hrs	7 Days
No. of coats	Generally, one to two coats		
Type	Acrylic emulsion		
Gloss levels	Matt		
Specific Gravity	~ 1.25-1.3		
Thinner	Water – not recommended		
Shelf Life	24 months from date of mfg (sealed)		

## Important Information

- Must only be applied in air temperatures between 10oC and 30oC on a dry substrate and must be protected from rain and frost for the first 24 hours or finished work must be protected from rain, frost and severe weather conditions until fully dried.
- Avoid application in full sun or hot, windy conditions.

## Safety and Handling

Refer to Material Safety data sheet and warranty document before use

- Avoid inhalation of the vapour, prolonged skin contact and particularly eye contact
- Wear protective clothing to minimize skin contact and wear goggles where splatter is likely
- Where spills occur, soak up liquid spillage with sand/sawdust and dispose of in a sensible manner. Do not permit run-off to sewer, storm water or open bodies of water
- **Storage:** Store away from food and drink and in a safe place

For further information or Material Safety Data Sheet, please call (03) 9364 4489 or visit [www.ultratexvic.com.au](http://www.ultratexvic.com.au)

