

Safety Data Sheet

Primer



15A Malcolm Crt, Kealba 3021
(03) 9364 4489
ultra.tex@hotmail.com
ABN: 50 119 993 412

Section 1.	Material Information
Product Name:	Primer
Manufacturer:	Ultratex Wall Cladding & Coating Pty Ltd
Recommended Use:	Primer (undercoat)
Emergency Contact:	131 126

Based on available information, not classified as hazardous according to criteria of NOHSC.

Not classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail.

Section 2.	Hazard Identification
Poison Schedule:	None allocated.

Section 3.	First Aid Measures
Inhalation:	Remove victim from area of exposure - avoid becoming a casualty. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. Seek medical advice if effects persist.
Skin Contact:	If skin contact occurs, remove contaminated clothing and wash skin with running water. If irritation occurs seek medical advice.
Eye Contact:	If in eyes, wash out immediately with water. In all cases of eye contamination, it is a sensible precaution to seek medical advice.
Ingestion:	Rinse mouth with water. If swallowed, give a glass of water to drink. If vomiting occurs give further water. Seek medical assistance.
Notes to physician:	Treat symptomatically.

For advice, contact a Poisons Information Centre (Phone - Australia 131 126) or a doctor.

Section 4. Composition / Information of Ingredients

Components	CAS Number	Proportion
Pigments		0-30%
Synthetic emulsion Polymer(s)		10-50%
Calcium Carbonate	471-34-1	50-80%
Water	7732-18-5	10-40%
Ingredients determined not to be hazardous		to 100%

Section 5. Fire Fighting Measures


Specific Hazards:	Non-combustible material.
Fire-fighting advice:	Non-combustible material, however, following evaporation of the water component of the material, the residual material can burn if ignited. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion.
Suitable Extinguishing Media:	Water fog (or if unavailable fine water spray), foam, dry agent (carbon dioxide, dry chemical powder).

Section 6. Accidental Release Measures

Slippery when spilt. Avoid accidents, clean up immediately.
Wear protective equipment to prevent skin and eye contact. Contain - prevent run off into drains and waterways.
Use absorbent (soil, sand or other inert material). Collect and seal in properly labeled containers or drums for disposal. If contamination of sewers or waterways has occurred advise local emergency services.

Section 7. Handling and Storage

Handling advice:	Avoid eye contact and repeated or prolonged skin contact. Keep containers tightly closed
Storage advice:	Store in cool place and out of direct sunlight. Keep containers closed when not in use - check regularly for leaks.

Section 8. Exposure Controls / Personal Protection	
Occupational Exposure Limits:	No value assigned for this specific material by the National Occupational Health and Safety Commission.
Engineering Control Measures:	Provide adequate ventilation. If using indoors, keep windows and doors open during use. Keep containers closed when not in use.
Personal Protective Equipment:	Wear overalls, safety glasses and impervious gloves. 

Section 9. Physical and Chemical Properties	
Physical state:	Viscous liquid
Colour:	White or Coloured
Solubility:	Miscible with water
Specific Gravity:	1-1.9 @20°C
Relative Vapour Density (air=1):	>1
Vapour Pressure (20 °C):	Not Available
Flash Point (°C):	Not Applicable
Flammability Limits (%):	Not Applicable
Autoignition Temperature (°C):	Not Applicable
% Volatile by Volume:	Not Available
Solubility in water (g/L):	Miscible
Melting Point/Range (°C):	Not Applicable
Boiling Point/Range (°C):	100 (water)
Decomposition Point (°C):	Not Available
pH:	8-10
Viscosity:	Not Available
Evaporation Rate:	Not Available

Section 10. Stability and Reactivity	
Stability:	No information available.
Section 11. Toxicological Information	
No adverse health effects are expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:	
Ingestion:	No adverse effects expected, however large amounts may cause nausea and vomiting.
Eye contact:	May be an eye irritant.
Skin contact:	Contact with skin may result in irritation.
Inhalation:	Where this material is used in a poorly ventilated area, at elevated temperatures or in confined spaces, vapour may cause irritation to mucous membranes of the respiratory tract, headache and nausea. Breathing in mists or aerosols may produce respiratory irritation.
Toxicological Data:	No LD50 data available for the product.
Section 12. Ecotoxicological Information	
Avoid contaminating waterways.	
Section 13. Disposal Considerations	
Disposal methods:	Refer to Waste Management Authority. Dispose of material through a licensed waste contractor. Normally suitable for disposal at approved land waste site.
Section 14. Transport Information	
Road and Rail Transport:	Not classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail.
Marine Transport:	Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.
Air Transport:	Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.
Section 15. Regulatory Information	
Classification:	Based on available information, not classified as hazardous according to criteria of NOHSC.
Poisons Schedule:	None allocated.

All the constituents of this material are listed on the Australian Inventory of Chemical Substances (AICS).

Section 16. Other Information	
This material safety data sheet has been prepared by Ultratex Wall Cladding & Coatings Pty Ltd - Technical Department	
Reason(s) for Issue:	Revised MSDS

This MSDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since Ultratex cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material.

If clarification or further information is needed, the user should contact Ultratex using the contact details on page 1. Ultratex Wall Cladding & Coatings Pty Ltd.'s responsibility for the material as sold is subject to the terms and conditions of sale, a copy of which is available upon request