

Technical Data Sheet

Venetian Polish

Plaster



15A Malcolm Crt, Kealba 3021

(03) 9364 4489

ultra.tex@hotmail.com

ABN: 50 119 993 412

Description

VENETIAN PLASTER -decorative tints - contains real marble dust which adds to the beauty of the finish. Traditional Venetian plaster is made of lime or gypsum and applied over laths, which are horizontal strips of wood, fastened to the joists and studs of a wall. Venetian Polish becomes fully washable three weeks after application. It is non-toxic. You control the sheen level of the finish by the amount of sanding and burnishing done on the finish plaster coat. Various looks are possible with the Venetian Plaster system, such as polished marble, stone, or suede. The more the surface is polished the more translucent the finish becomes; this translucency creates the depth seen in real marble. The finish is so smooth it feels like genuine marble. In fact, Venetian Plaster was formulated to imitate a complicated 'Old World' Italian technique called "Scagliola".

Uses

Thinner: Ready to use

Application Method: Venetian Stainless-Steel Trowel

Drying Time: 12 hours, Dry to Recoat 12 hours

Flammability: Not flammable

If swallowed, immediately contact a doctor and show him the packaging and labelling

Composition

- Long-seasoning slaked lime
- High-selected calcareous filler
- Non-toxic additives

Disposal

Dispose of in accordance with local council regulations

Technical Data

Viscosity: Thixotropic

Complete drying: 24 hours at 20°C

Temperature of application: between 10°C and 30°C

Colours: to be chosen

Yield: 1.2 to 1.5m² per 1kg

Package: 15L pail

Application

Surface preparation

The application on lime supports is recommended, but it can also be applied on plaster or by-products, and old hydro paints, only if strong and well-fixed, after the application of a coat of primer.

Application

Spread a coat of Venetian polish with a stainless-steel smoother to level the support; if needed, spread a second coat. Apply little spots of product and then take them away ("put and remove" technique); when the product is going to dry up, press and move to polish, until the desired result is obtained. Multiple coats can be applied for extra durability and protection in wet areas.

Safety and Handling

Skin contact: Thoroughly wash with soap and warm water before the coating dries. Individuals with sensitive skin may require gloves.

Eye contact: Rinse with clean water for 15 minutes. Seek medical attention.

Inhalation: To help prevent inhalation, use only in well-ventilated areas. If inhalation occurs, move to fresh air. If irritation persists, seek medical attention.

Ingestion: Do not induce vomiting. Seek medical attention.

CAUTION: KEEP OUT OF THE REACH OF CHILDREN. Do not take internally. Dispose of in accordance with local council regulations

Transport and Storage

Store in a cool, dark place.

Do not stack over 3 high.

Keep pail sealed.