

Technical Data Sheet

Wax



15A Malcolm Crt, Kealba 3021
(03) 9364 4489
ultra.tex@hotmail.com
ABN: 50 119 993 412

Description

WAX is a transparent water-based paste wax for the protection of specific synthetic and Venetian plaster with lime. Application produces a higher gloss polished stucco which provide the wash ability and water resistance, also giving it a greater uniformity of final colour. It is non-toxic VOC (<80) L/A 200g/l (2010).

Method of Application

- Apply directly on the venation plaster or concrete finish, thinly, with a stainless steel spatula, and then polish with a stainless steel spatula
- Leave to absorb and dry at least 2 hours and then proceed to final levelling always with a stainless steel spatula
- For further treatment, the surface must be clean and completely dry; ideal temperature for application 15–25°C.
- Apply thinly and evenly with a woollen or cotton cloth

Technical Data

- **Thinner:** Water
- **Specific weight:** 0,962 kg/lit +/- 1%
- **Viscosity:** Thixotropic paste
- **Composition:** Special emulsion water-based wax, non-toxic additives.
- **Drying:** Touch dry after 2 hours at 20°, completely dry 24 hours at 20°
- **Application temperature:** Between 5°C and 30°C
- **Yield:** 15 m2/lit
- **Colour:** Transparent
- **Package:** In buckets of 1 lit
- **Application:** Apply with a special stainless-steel spatula
- **Preservation:** 24 months in the intact package, away from temperature changes
- **Ingestion:** If swallowed, immediately contact a doctor and show him the packaging and labelling